



MAN02-A Manometer for Differential Pressure

The Amprobe MAN02-A is a portable, battery operated pressure measuring device. The right tool for HVAC/R technicians measuring pressure level, or anyone working with valves, control sensors in a pneumatic control environment.

Large dual digital display shows gauge or differential pressure values. It also has a relative time clock for measuring when events happen. Such as minimums and maximum values. Or use the USB port output to record continuous measurement values. (USB cable sold separately.) Amprobe's Download Suite software available online.

- Reads gauge and differential pressure
- Five selectable units of measure: InH₂O, psi, mbar, bar, mmH₂O
- Ideal for measuring HVAC/R pressure levels
- Also used for Pneumatic controls
- Offers Maximum and Minimum value recordings, Data Hold
- Auto power off function, Large backlight LCD
- Built-in USB port downloads information to your PC with optional PC cable and Amprobe's free Download Suite software
- Includes connection hoses

No hassle warranty

No waiting.

No shipping charges.



Our commitment to high-quality products and customer service is demonstrated by our industry exclusive "No Hassle" warranty. In the unlikely event that an Amprobe Test Tool requires warranty service, any of our local dealers are authorized to replace it, on the spot.

(note: \$500 MSLP limit)

MAN02-A Manometer for Differential Pressure**Data Sheet****Specifications**

General	
Range	0 to ± 2 Psi
Accuracy	$\pm 0.3\%$ full scale at 25°C (77°F)
Response Time	0.5 second
Sensitivity Resolution	per 0.401 in of H ₂ O 0.001 per 0.0145 Psi 0.1 per mbar
Battery Life	14 hours
Electrical	
Battery	1 x 9V Alkaline Battery (NE DA 1604A, IE C 6LR61) included
Mechanical	
Dimension	182 x 72 x 30 mm (7.16 x 2.83 x 1.18 in)
Weight	0.220 Kg (0.485 lb)
Case	Hard Carrying Case
Environmental	
Operating Humidity	80% RH
Operating Temperature	0 to 50°C / 32 to 122°F
Storage Temperature	-20 to 60°C / -4 to 140°F
Agency Approvals & Certifications	
	CE

INCLUDED PARTS

Carrying Case
Connection Hoses (2)

Optional Accessories

TM-SWA-USB Download Suite Software with USB Cable

Amprobe® Test Tools
website: www.Amprobe.com
email: info@amprobe.com
Everett, WA 98203
Tel: 877-AMPROBE

Amprobe® Test Tools Europe
Amprobe Test Tools Europe
Beha-Amprobe GmbH
In den Engematten 14
79286 Glottertal, Germany
Tel.: +49 (0) 7684 8009 - 0

©2008 Amprobe Test Tools. All rights reserved.
4/2009 3358099 Rev B



MAN30 Differential Pressure Manometer

Hand held, accurate and featuring an internal time clock to capture events, these products are designed for HVAC/R technicians or other pneumatic control environment.

- Measuring range up to 30 PSI (206.9 kPa)
- Necessary tool for gauge and differential pressure measurement
- Perfect for applications such as: valves, control sensors in a pneumatic control environment, HVAC/R pressure levels and medical pressure systems
- 11 selectable units of measure: bar, mmHg, ozin2, kgcm2, psi, inH2O, kpa, ftH2O, inHg, cmH2O, mbar
- Maximum and Minimum value recordings with time stamp help adjust and trouble shoot the pressure systems
- Data Hold
- Large backlight LCD
- Auto power off function
- Built-in computer USB port for data downloads with optional PC cable and software
- Includes connection hoses

No hassle warranty

No waiting.

*No shipping
charges.*



Our commitment to high-quality products and customer service is demonstrated by our industry exclusive "No Hassle" warranty. In the unlikely event that an Amprobe Test Tool requires warranty service, any of our local dealers are authorized to replace it, on the spot.

(note: \$500 MSLP limit)





MAN30 Differential Pressure Manometer

Data Sheet

Specifications

General	
Accuracy	Max 1% full scale at 25°C (77°F)
Response Time	0.5 second
Sensitivity	
Resolution	0.01 psi / 0.1kpa / 0.5mmHg / 0.001 kg/cm ² 1 hpa / mbar, 0.001 bar, 0.3inH ₂ O, 1cmH ₂ O, 0.02 ftH ₂ O, 0.2 oz/inch ²
Battery Life	14 hours
Electrical	
Battery	1 X 9V Alkaline Battery (NE DA 1604A, IE C 6LR61) included
Mechanical	
Dimension	182 x 72 x 30 mm (7.16 x 2.83 x 1.18 in)
Weight	0.220 Kg (0.485 lb)
Case	Hard Carrying Case
Environmental	
Operating Humidity	80% RH
Operating Temperature	0°C to 50°C / 32°F to 122°F
Storage Temperature	-20°C to 60°C / -4°F to 140°F
Agency Approvals & Certifications	CE

Amprobe® Test Tools

website: www.Amprobe.com
email: info@amprobe.com
Everett, WA 98203
Tel: 877-AMPROBE

Amprobe® Test Tools Europe

In den Engematten 14
79286 Glottertal, Germany
Tel.: +49 (0) 7684 8009 - 0

©2009 Amprobe Test Tools. All rights reserved.
7/2009 3520439 Rev A