



DELMHORST
EUROPE
WHEN ACCURACY IS THE POINT.[™]
FX-2000 Baler
moisture meter hay



This state-of-the-art moisture meter for hay is ideal for high-volume producers who need the time-saving convenience of on-the-go monitoring. Whether in the windrow, on-the-go while baling, or in the bale, the FX-2000 gives clear, accurate moisture readings every step of the way!

Your Benefits:

- Bright, clear digital display
- Can be used for on-the-go moisture monitoring or as a portable meter
- In continuous mode:
 - Takes two readings every second
 - Displays the average and highest of eight accumulated readings
 - Readings updated every 4 seconds
 - Built-in back light
 - Connects to tractor power supply
- In portable mode:
 - Averages up to 100 accumulated readings
 - Displays average and highest of accumulated readings
- Moisture Range: 6%-40% on hay
- Built-in calibration check
- Audible, adjustable alarm alerts you when a pre-selected MC has been reached
- Operating Temperature: from 0°C to 50°C
- Size: 20x8x4cm (8x3x1⁵/₈"
- Weight: 285gr. (10 oz)
- Rugged construction ensures years of reliable use
- Optional sturdy plastic carrying case
- 9V battery
- 3-year warranty



Special Packages:

Moisture meter **FX-2000 value** Package:

Includes meter with power supply, 1986 bale sensor with cable and mounting bracket.

Moisture meter **FX-2000 Deluxe** Package:

Includes meter with power supply, 1986 bale sensor with cable and mounting bracket, H-4 handle, 830-2 25cm (10") pen electrode, 831 windrow electrode, and carrying case.

Moisture meter **FX-2000 Deluxe 18** Package:

Includes meter with power supply, 1986 bale sensor with cable and mounting bracket, H-4 handle, 830-3 45cm (18") pen electrode, 831 windrow electrode, and carrying case.

Includes meter, H-4 handle, 830-3 45cm (18") pen electrode, 831 windrow electrode and carrying case



Available electrodes:



1235

Pen electrode available in 2 lengths:
1235 – 25cm (10")
1235/18 – 45cm (18")
(Attaches directly to the connector on top of the meter).
For moisture measuring in standard bales.



830-X

Pen electrode available in different lengths:
830-2 – 25cm (10")
830-3 – 45cm (18")
830-4 – 90cm (36")
(Requires H-4 Handle)
For moisture measuring in standard and high density bales



831

Short needle electrode
(requires H-4 Handle)
For testing MC of hay in the windrow.



H-4

Handle for electrodes 830-x and 831.
Two handed operation is recommended over using an electrode that connects directly to the top of the meter (like our 1235 series) to minimize stress placed on the meter casing.



1986

Comes with 900cm (30') cable to run from the sensor mounted in the bale chamber to the meter in the cab.
Also available as 1986/40 with 1200cm (40') cable for larger balers.
For continuous monitoring during baling.



2110

Split bale chamber sensor.
For use with Freeman balers.



MCS-4

This moisture content standard is great for verifying that your F-series moisture meter is in calibration. With two electrical resistance values (16% and 22%) to test your meter against, you can be sure that your readings will stand up to the strictest standards of accuracy.