

Cable Ladder System

GUARDIAN
FALL PROTECTION

Part #	Length	Description
04810	100'	Cable Ladder System Kit
04820	200'	Cable Ladder System Kit
04830	300'	Cable Ladder System Kit

Compliant with all applicable OSHA 1910, OSHA 1926 Subpart M, ANSI Z359.1-2007, and ANSI A10.32-2012 regulations.

Materials: Galvanized steel.

System Contents:

- (3) Mounting Brackets.
- (6) U-Bolts.
- (12) Nuts with Lock Washers (for U-Bolts).
- (1) Small U-Bolt (for bottom assembly attachment).
- (2) Nuts with Lock Washers (for Small U-Bolt).
- (1) Intermediary Cable Bracket per 25' of Cable.



Personal Fall Arrest: Cable Ladder Systems may be used to support a MAXIMUM 1 Personal Fall Arrest System (PFAS) for use in Fall Arrest applications. Structure must withstand loads applied in the directions permitted by the system of at least 5,000 lbs. Maximum free fall is 18". Maximum distance between harness D-ring and fall arrester is 9". Applicable D-ring: Chest.

MAXIMUM 1 user per Cable Ladder System.

User capacity range: 130-310 lbs. (including all clothing, tools, and equipment).

MUST be used in combination with compatible fall arrester, such as a Guardian Fall Protection Cable Grab (#01510).

ALWAYS read and understand all manufacturer's instructions provided with equipment at time of shipment.

