

# Velocity SRL-LE

## Part # 10946

Compliant with all OSHA 1910, OSHA 1926 Subpart M, ANSI Z359.14-2014, and ANSI A10.32-2012 regulations.

Repairable by manufacturer representative only.  
Contact customer service for details.

Velocity SRL-LE is suitable for the following applications:



**Personal Fall Arrest:** Velocity SRL-LEs may be used to support a MAXIMUM 1 Personal Fall Arrest System (PFAS) for use in Fall Arrest applications. Structure must withstand loads applied in the directions permitted by the system of at least 5,000 lbs. Applicable D-ring: Dorsal.

- Free fall, LE Use: Maximum 6'. Please note that free fall in excess of 2' is not in compliance with ANSI A10.32-12 fall protection regulations, but is still fully compliant with all applicable ANSI Z359.14-14, OSHA 1926 Subpart M, and OSHA 1910 regulations.

- Free fall, non-LE Use: Not permitted.



**Restraint:** Velocity SRL-LE may be used in Restraint applications. Restraint systems prevent workers from reaching the leading edge of a fall hazard. Always account for fully deployed length of lanyard/SRL. Structure must withstand loads applied in the directions permitted by the system of at least 1,000 lbs. No free fall is permitted. Restraint systems may only be used on surfaces with slopes up to 4/12 (vertical/horizontal). Applicable D-rings: Dorsal, Chest, Side, Shoulder.

**For all applications, worker weight capacity range  
(including all clothing, tools, and equipment):**

**LE Use: 130-310 lbs.**

**Non-LE Use: 130-420 lbs.**



**WARNING** Use of equipment in unintended applications may result in serious injury or death. Maximum 1 attachment per connection point.

Materials: galvanized steel, zinc-plated steel, polyester, and nylon.

Lifeline: Galvanized steel cable, 3/16" diameter.

Average arresting force: 900 lbs.

**LE Use:**

Min. setback distance from edge: 6'

Max. arresting distance: 54" - 102"

Min. fall clearance: 17' - 21'

**Non-LE Use:**

Max. arresting distance: 54"

Min. fall clearance: 9'

Class B SRL

MAXIMUM 1 user per Velocity SRL-LE.

**GUARDIAN**  
FALL PROTECTION

