

Velocity SRL

GUARDIAN
FALL PROTECTION

| Part # | Length | Description |
|--------|--------|--|
| 42000 | 16' | 3/16" Galvanized Cable SRL w/Carabiner, Swivel Top, & Snap Hook |
| 42001 | 20' | 3/16" Galvanized Cable SRL w/Carabiner, Swivel Top, & Snap Hook |
| 42002 | 30' | 3/16" Galvanized Cable SRL w/Carabiner, Swivel Top, & Snap Hook |
| 42003 | 50' | 3/16" Galvanized Cable SRL w/Carabiner, Swivel Top, & Snap Hook |
| 42004 | 80' | 3/16" Galvanized Cable SRL w/Carabiner, Swivel Top, & Snap Hook |
| 42005 | 100' | 3/16" Galvanized Cable SRL w/Carabiner, Swivel Top, & Snap Hook |
| 42006 | 20' | 1" Nylon Webbing w/Carabiner, Swivel Top, & Snap Hook |
| 42008 | 40' | 1" Nylon Webbing w/Carabiner, Swivel Top, & Snap Hook |
| 10950 | 10' | 3/16" Galvanized Cable SRL w/Carabiner, Swivel Top, & Snap Hook |
| 10951 | 10' | 3/16" Galvanized Cable SRL w/Carabiner, Swivel Top, & Aluminum Rebar Hook |
| 10957 | 10' | 3/16" Nylon Coated Galvanized Cable SRL w/Carabiner, Swivel Top, & Snap Hook |



Compliant with all OSHA 1910, OSHA 1926 Subpart M, ANSI Z359.14-2014, and ANSI A10.32-2012 regulations.

Only repairable by manufacturer representative.
Contact customer service for details.

Velocity SRL is suitable for the following applications:



Personal Fall Arrest: Velocity SRLs may be used in Personal Fall Arrest applications as a component of a MAXIMUM 1 Personal Fall Arrest System (PFAS). Structure must withstand loads applied in the directions permitted by the system of at least 5,000 lbs. No free fall is permitted. SRL must always be positioned at or above harness dorsal D-ring AND at or below anchor point. Applicable D-ring: Dorsal.



Restraint: Velocity SRLs may be used in Restraint applications. Restraint systems prevent workers from reaching the leading edge of a fall hazard. Always account for fully deployed length of lanyard/SRL. Structure must withstand loads applied in the directions permitted by the system of at least 1,000 lbs. No free fall is permitted. Restraint systems may only be used on surfaces with slopes up to 4/12 (vertical/horizontal). Applicable D-rings: Dorsal, Chest, Side, Shoulder.

**For all applications, worker weight capacity range
(including all clothing, tools, and equipment): 130-310 lbs.**



WARNING Use of equipment in unintended applications may result in serious injury or death. Maximum 1 attachment per connection point.

NEVER for use in Leading Edge (LE) applications.

Materials: stainless steel, galvanized steel, polyester, and glass-filled nylon.

Max. arresting distance: 54"

Min. fall clearance: 9'

Class B SRL

MAXIMUM 1 user per Velocity SRL.