

## Diablo Tie-Back

Part #	Length	Description
11020	9'	Diablo Tie-Back SRL, Single Leg.
11056	9'	Diablo Tie-Back SRL, Dual Leg Kit.
99-05-0015	8.25'	Diablo Tie-Back SRL, Single Leg.

Compliant with all OSHA 1910, OSHA 1926 Subpart M, ANSI Z359.1-2007., and ANSI A10.32-2012 regulations.

Diablo Tie-Back is suitable for the following applications:



**Personal Fall Arrest:** Diablo Tie-Back SRL may be used to support a MAXIMUM 1 PFAS for use in Fall Arrest applications. Structure must withstand loads applied in the directions permitted by the system of at least 5,000 lbs. No free fall is permitted. SRL must always be positioned at or above harness dorsal D-ring AND at or below anchor point. Applicable D-ring: Dorsal.



**Restraint:** Diablo Tie-Back SRL may be used in Restraint applications. Restraint systems prevent workers from reaching the leading edge of a fall hazard. Always account for fully deployed length of lanyard/SRL. Structure must withstand loads applied in the directions permitted by the system of at least 1,000 lbs. No free fall is permitted. Restraint systems may only be used on surfaces with slopes up to 4/12 (vertical/horizontal). Applicable D-rings: Dorsal, Chest, Side, Shoulder.



**For all applications: worker weight capacity range (including all clothing, tools, and equipment) is 130-420 lbs.**



**WARNING** Use of equipment in unintended applications may result in serious injury or death. Maximum 1 attachment per connection point.

Materials: galvanized steel, aluminum, glass-filled nylon, polyester, and nylon.

Class A SRL

Average arrest force: 1,350 lbs.

Maximum arrest force: 1,800 lbs.

Maximum deceleration distance: 24"

May be used in either tie-back or non-tie-back applications. In non-tie-back applications, anchor point to which Diablo Tie-Back is attached must be a minimum 3' above harness dorsal D-ring.

MAXIMUM 1 user per Diablo Tie-Back SRL