

## DOUBLE DIABLO SRL KIT 2.0

SELF-RETRACTING LIFELINE

FOR MORE INFO, PLEASE CALL  
1.800.466.6385 OR VISIT [GUARDIANFALL.COM](http://GUARDIANFALL.COM)

**NEW!**

**OLD**



## ▶ SPECS

### STANDARDS:

OSHA 1926 SUBPART M & 1910 | ANSI Z359.14-14 & A10.32-12

### MATERIAL:

POLYESTER, STAINLESS STEEL  
ALUMINUM, & NYLON

### REMINDERS:

- ONLY 1 USER PER SRL
- ALWAYS MAINTAIN 100% TIE-OFF
- FOR DUAL LEG KIT, ASSEMBLE AND USE ACCORDING TO INSTRUCTIONS PROVIDED WITH DUAL SRL BRACKET.

### CAPACITY:

130 - 420 LBS.

### STATISTICS:

- CLASS A SRL
- AVERAGE ARREST FORCE: 1,350 LBS.
- MAXIMUM ARREST FORCE: 1,800 LBS.
- MAXIMUM DECELERATION DISTANCE: 24"

## OLD PART #'S:

11016

11017

11018

11019

11051

11052

11053

11054

## NEW PART #'S:

11080

11081

11082

11083

11084

11053

11086

11087

OLD:



NEW:



## DESCRIPTION: DOUBLE DIABLO WEB SRL'S WITH STEEL REBAR HOOKS

PART #: **11087**

WEIGHT: **7.75 LBS**

LENGTH: **6'**

### THE DOUBLE DIABLO SRL IS SUITABLE FOR THE FOLLOWING APPLICATIONS:



#### • PERSONAL FALL ARREST:

Diablo SRL may be used in Personal Fall Arrest applications to support:

- MAXIMUM 1 Personal Fall Arrest System (PFAS). Structure must withstand loads applied in the directions permitted by the system of at least 5,000 lbs.
- Maximum permitted free fall is 2' (SRL may be positioned no more than 2' below harness dorsal D-ring or 2' above anchor point).



#### • RESTRAINT:

Diablo SRLs may be used in Restraint applications. Restraint systems:

- Prevent workers from reaching the leading edge of a fall hazard.
- Always account for fully deployed length of SRL. Structure must withstand loads applied in the directions permitted by the system of at least 1,000 lbs.
- No free fall is permitted.
- May only be used on surfaces with slopes up to 4/12 (vertical/horizontal).
- Applicable D-rings: Dorsal, Chest, Side, Shoulder.