

Alligator Guardrail System

Part #	Description
15167	Alligator Clamp System. Includes 47" G-Rail Post (15163) & Extended Guardrail Gusset (61027).
61074	7' - 10' Adjustable Snap-On Metal Guardrail.
61075	4' - 7' Adjustable Snap-On Metal Guardrail.
15161	Alligator Cart. Carries complete 350' Kit.
15162	350' Kit. Includes: (36) 15167, (8) 61075, (72) 61074, (36) 15163, (1) 61027, & (1) 15161.
15168	350' Kit. Includes: (36) 15167, (8) 61075, (72) 61074, (36) 15163, & (1) 61027. Does not include cart.
61027	Extended Guardrail Gusset.



Compatible with OSHA 1910 and OSHA 1926 Subpart M regulations.



Alligator Guardrail Systems may be used in Fall Prevention applications ONLY. Fall Prevention Systems are placed around the leading edges of any and all fall hazards to prevent a worker from going over an edge, and may be used in substitute of Fall Protection or safety netting systems. Installation requirements for Alligator Guardrail Systems set forth in equipment instructions MUST be adhered to. Personal Fall Arrest, Work Positioning, Climbing, Rescue, and any other systems must NEVER be connected to Fall Prevention Systems.

Surfaces more than 6' above lower levels require the use of a Fall Prevention or Fall Protection system.

Suitable for use in Pitched and Barrel Roof, Flush Mount Roof, Parapet Wall, and Gusset installation applications. Refer to instructions for application-specific installation procedures.

Maximum spacing between guardrail post receivers is 8'.

Substrate Limitations:

- Alligator Guardrail System may only be installed on roofs with pitches of flat, 3/12, 6/12, and 9/12. NEVER use on surfaces with pitches greater than 9/12.
- Wood substrate MUST be 1/2" CDX or better. Metal substrate MUST be 24 gauge or better.
- Parapets MUST be between 2" - 16" in width, and a minimum 7" in height.

Guardrails:

Compatible with Adjustable Snap-On Metal Guardrails (part #s: 61074 & 61075), or 2" x 4" construction grade lumber or better. Refer to instructions for guardrail installation.

