

4-Person Rope HLL

Part #: 30800

Compliant with all OSHA 1910, OSHA 1926 Subpart M, ANSI Z359.1-2007, and ANSI A10.32-2012 regulations.

4-Person Rope HLL is suitable for the following applications:



Personal Fall Arrest: 4-Person Rope HLLs may be used to support a MAXIMUM 4 Personal Fall Arrest Systems (PFAS) for use in Fall Arrest applications. Structure must withstand loads applied in the directions permitted by the system of at least 5,000 lbs. Maximum free fall is 6'. Applicable D-ring: Dorsal.



Restraint: 4-Person Rope HLLs may be used in Restraint applications. Restraint systems prevent workers from reaching the leading edge of a fall hazard. Always account for fully deployed length of lanyard/SRL. Structure must withstand loads applied in the directions permitted by the system of at least 1,000 lbs. No free fall is permitted. Restraint systems may only be used on surfaces with slopes up to 4/12 (vertical/horizontal). Applicable D-rings: Dorsal, Chest, Side, Shoulder.



For all applications: worker weight capacity range (including all clothing, tools, and equipment) is 130-310 lbs.

NEVER for simultaneous use in Fall Arrest and Restraint.



WARNING

Use of equipment in unintended applications may result in serious injury or death.

Materials: Polyester and powder-coated aluminum.

Maximum 4 connections per 4-Person Rope HLL.

UPC-A Code: 672421308005