

1880-2400.pdf

Model #: 1880-2400
UPC: #049448188024
MSRP: \$244.00



IP 65 dust and waterproof, Extremely accurate with .05 degree at 0 degrees and 90 degrees and quick horizontal and vertical calibration, Angle inclination in 5 construction languages - units of measure (degrees, percent, in/ft (fractional), in/ft (decimal), mm/m, Automatic digit inversion for overhead measurements and working range on angle measurement is 0 x 90 degrees, Reference function making any slope "0.0" and hold function locks measurement on the LCD, SurroundView® vials reflect ambient light for easy-read, 1880-2400 Includes > Digital level, instruction manual and soft-sided pouch, Models : 1880-2400 24" Digital Level, 1880-4800 48" Digital Level

PRODUCT DETAILS

1880-2400 Includes: Digital level, instruction manual and soft-sided pouch

- IP 65 dust and waterproof
- Extremely accurate with .05 degree at 0 degrees and 90 degrees and quick horizontal and vertical calibration
- Angle inclination in 5 construction languages - units of measure (degrees, percent, in/ft (fractional), in/ft (decimal), mm/m
- Quick horizontal and vertical calibration
- Reference function making any slope "0.0"
- Hold function locks measurement on the LCD
- Working range on angle measurement 0 x 90°

SPECIFICATIONS

Accuracy	$\pm 0.05^\circ$ for 0° and 90° , $\pm 0.1^\circ$ for other angles
Battery Life	Approximately 100 hours continuous use
Dimensions	24" x 1" x 2.4" (610 x 25 x 61mm)
IP Protection Class	65
Power Supply	2 "AAA" Alkaline Batteries (not included)
	0.05° or 0.1°
	0.09% or 0.2%
Resolution	$1/8"$
	0.9mm/m or 2mm/m
	$0.125"$
Warranty	Limited lifetime warranty with store receipt
Weight	1.19 lbs. (0.54kg)
Working Range	0° to 90°
Working Temperature	14°F to 122°F (-10°C to $+50^\circ\text{C}$)