

40-6519 English.pdf|40-6519 French.pdf|40-6519 Spanish.pdf

Model #: 40-6519
UPC:
MSRP:



Horizontal self-leveling. Manual-leveling in the vertical plane. Split beam establishes a 90 degree angle. Includes laser detector. 40-6519 INCLUDES > laser, 6 "AA" alkaline batteries, detector with 2 "AAA" alkaline batteries and clamp, tinted glasses, magnetic target, 8 ft. grade rod, elevating tripod, instruction manual, hard-shell carrying case.

PRODUCT DETAILS

- Horizontal self-leveling
- Manual-leveling in the vertical plane
- Split beam establishes a 90 degree angle
- Includes laser detector

SPECIFICATIONS

Accuracy	±3/16"/50'
Battery Life	25 hours continuous use
Dimensions	5.70" x 4.20" x 6.20"
Exterior Range	Up to 800' with detector (included)
Interior Range	Up to 200'
IP Protection Class	IP 54
Laser Classification	Class IIIa
Laser Wavelength	635nm±10nm (Red)
Leveling Method	Self-Leveling (Pendulum)
Maximum Power Output	≤5mW
Power Supply	6 "AA" alkaline batteries (included)
Rotation Speeds	200, 500, 800 RPM
Self-Leveling Range	±3°
Warranty	3 Years
Weight	3.10 lbs.
Working Temperature	14° F to 113° F



APPLICATION

The Johnson Level 40-6519 can be used for the following indoor and outdoor applications; leveling, checking cut and fill, setting foundations and footings, concrete pours, septic tanks and basement excavations, acoustical ceiling and drywall, align and plumb walls, metal stud and wood framers, level deck floors, establish diagonals and footings, contour framing, drainage, terracing and retaining walls.



For additional information on Johnson products, please contact
Customer Service at 888.953.8357 or service@johnsonlevel.com
www.johnsonlevel.com | © Johnson Level & Tool Mfg. Co. Inc.