

40-6546.pdf

Model #: 40-6546
UPC: 049448065462
MSRP: \$2,336.58



Green beam is 400% more visible than red beam, Designed for indoor and outdoor applications, Electronically-controlled dual slope feature, Electronic self-leveling horizontally and vertically, Laser beam modes include four adjustable line lengths and three rotational speeds, Three rotational speeds: 0, 300 and 800 RPM, Visual and audible alarms when beyond leveling range, Height of Instrument/Tilt alarm function ensures product accuracy.

PRODUCT DETAILS

- Green beam is 400% more visible than red beam
- Designed for indoor and outdoor applications
- Electronically-controlled dual slope feature
- Electronic self-leveling horizontally and vertically
- Laser beam modes include four adjustable line lengths and three rotational speeds
- Three rotational speeds: 0, 300 and 800 RPM
- Visual and audible alarms when beyond leveling range
- Height of Instrument/Tilt alarm function ensures product accuracy
- 40-6546 Includes > Laser, Li-ion rechargeable battery pack, alkaline battery compartment (batteries not included), Li-ion battery adapter, remote control with 9V battery, wall/ceiling mount, magnetic target, tinted glasses, instruction manual with warranty card, hard-shell carrying case

SPECIFICATIONS

Accuracy	+/-1/16"/100ft. (+/-1.5mm/30m)
Auto-Leveling Range	+/- 5 degrees
Battery Life	Approximately 25 hours with Li-ion rechargeable battery pack (included); 16 hours with alkaline batteries (not included)
Center Screw Thread	5/8"-11
Dimensions	8.62" x 6.30" x 7.95" (219 x 160 x 202mm)
Exterior Range	Up to 1400ft. (427m) diameter with detector
Interior Range	Up to 400ft. (120m) diameter depending on light conditions
IP Protection Class	66
Laser Classification	Class IIIa
Laser Wavelength	532nm+/-10nm (Green)
Leveling Method	Automatic (Electronic)
Maximum Power Output	Less than/Equal to 5mW
Power Supply	Li-ion rechargeable battery pack or adapter (included); 3 "C" alkaline batteries (not included)
Remote Range	Up to 200ft. (60m) diameter with remote
Rotation Speeds	0, 300 and 800 RPM
Slope	+/- 5 degrees
Warranty	3 Year Warranty
Weight	5.47lbs. (2.4kg)
Working Temperature	32 degrees to 104 degrees (0 degrees celsius to +40 degrees celsius)

APPLICATION

The Johnson Level 40-6546 can be used for the following indoor applications; layout of interior walls, check door and window heights, acoustical/drop ceilings, layout warehouse racking, room additions, drywall installation, partition installation, squaring floor and wall tiles, installing sprinkler systems, align and plumb walls, level floors, metal stud and wood framers, level cabinets, level shelving and countertops.