

40-6603.pdf

Model #: 40-6603
UPC: 049448066780
MSRP: \$69.99



Vertical and horizontal laser cross. Manual mode for use at any angle. Locking compensator protects pendulum during transport. Visual out-of-level indicator. 1/4"-20 tripod thread for use with most common tripods. 40-6603 INCLUDES > Laser, 2 "AA" alkaline batteries.

PRODUCT DETAILS

- Vertical and horizontal laser cross
- Manual mode for use at any angle
- Locking compensator protects pendulum during transport.
- Visual out-of-level indicator
- 1/4"-20 tripod thread for use with most common tripods

SPECIFICATIONS

Accuracy	±3/16"/30'
Battery Life	20 hours continuous use
Dimensions	2.4" x 2.9" x 3.0"
IP Protection Class	IP 50
Laser Classification	Class II
Laser Wavelength	635nm±10nm (Red)
Leveling Method	Self-Leveling (Pendulum)
Maximum Power Output	<1mW
Power Supply	2 "AA" alkaline batteries (included)
Warranty	2 Years
Weight	6.9 oz (without batteries)
Working Range	Up to 30'
Working Temperature	32° F to 104° F

APPLICATION

The Johnson Level 40-6603 can be used for the following indoor applications; flooring, cabinetry, drop ceiling installation, wainscoting, carpentry, tiling, electrical boxes and switches, drywall track/stud wall installation, setting drainage slope.