

40-6646.pdf

Model #: 40-6646
UPC: 049448066469
MSRP: \$99.99



Projects 2 plumb dots and 1 level dot. Tall profile for clearance of wood or metal drywall track. Locking compensator protects pendulum during transport. Visual out-of-level indicator. 1/4" tripod thread for use with most common tripods. Dust resistant construction. 40-6646 INCLUDES > Laser, 2 "AA" alkaline batteries.

PRODUCT DETAILS

- Projects 2 plumb dots and 1 level dot
- Tall profile for clearance of wood or metal drywall track
- Visual out-of-level indicator
- 1/4"-20 tripod thread for use with most common tripods
- Dust resistant construction
- Locking compensator projects pendulum during transport

SPECIFICATIONS

Accuracy	±1/8"/30'
Battery Life	20 hours continuous use
Dimensions	3.6" x 2.6" x 4.5"
IP Protection Class	IP 50
Laser Classification	Class II
Laser Wavelength	650nm±10nm (Red)
Leveling Method	Self-Leveling (Pendulum)
Maximum Power Output	≤1mW
Power Supply	2 "AA" alkaline batteries (included)
Self-Leveling Range	±5°
Warranty	2 years
Weight	9.9 oz (without batteries)
Working Range	Up to 100'
Working Temperature	32° F to 104° F



APPLICATION

The Johnson Level 40-6646 can be used for the following indoor applications; flooring, cabinetry, drop ceiling installation, wainscoting, carpentry, tiling, electrical boxes and switches, drywall track/stud wall installation, setting drainage slope.



For additional information on Johnson products, please contact
Customer Service at 888.953.8357 or service@johnsonlevel.com
www.johnsonlevel.com | © Johnson Level & Tool Mfg. Co. Inc.