

Self-Leveling Rotary Laser System

Model #: 99-026K
UPC: 049448990269
MSRP: \$718.00



800' working diameter- over 11 acres! Includes everything to grade or level your jobsite. One person operation. Includes rechargeable batteries. Visual and audible alarms when beyond leveling range. Locking compensator protects inner mechanisms. 90° split beam for alignment work. Manual leveling in vertical plane. 99-026K Includes > Laser, NiMH rechargeable battery pack, 6V battery charger, detector with clamp and 9V battery, tripod, 13' grade rod, wall/ceiling mounting bracket, magnetic target, tinted glasses, instruction manual, hard-shell carrying case

PRODUCT DETAILS

- 800' working diameter- over 11 acres!
- Includes everything to grade or level your jobsite
- One person operation
- Includes rechargeable batteries
- Visual and audible alarms when beyond leveling range
- Locking compensator protects inner mechanisms
- 90° split beam for alignment work
- Manual leveling in vertical plane

SPECIFICATIONS

Accuracy	+/-1/8"/50ft.
Battery Life	Approximately 11 hours
Center Screw Thread	5/8"-11
Dimensions	4.96" x 6.69" x 6.61"
Exterior Range	Up to 800ft. diameter with detector
Interior Range	Up to 200ft. diameter
IP Protection Class	54
Laser Classification	Class IIIa
Laser Wavelength	635nm±10nm (Red)
Leveling Method	Self-leveling (Pendulum)
Maximum Power Output	≤5mW
Power Supply	NiMH rechargeable battery pack
Rotation Speeds	200, 400, 600 RPM
Self-Leveling Range	+/- 3 degrees
Warranty	3 Year Warranty
Weight	3.3lbs
Working Temperature	14 degrees to 113 degrees

APPLICATION

Perfect for residential excavations, landscaping, fence lines, wainscoting, drop ceilings.