



PYRAMEX
Perform At Your Peak



Ridgeline® Full Brim **ANSI CSA**

Shell constructed from ABS materials

Ratchet suspension is easy to adjust and allows the wearer to modify the fit while wearing hard hat

Replaceable suspensions and headbands available

4-point suspension may be converted to 6-point suspension with optional strap (HP6PTSUS)

Custom imprinting available on hard hats



Factory Direct Hydro Dipped

4-Point Ratchet Part No.	Color
HP54116 ●●	Matte White Graphite Pattern
HP54116S ●●	Shiny White Graphite Pattern
HP54117 ●●	Matte Black Graphite Pattern
HP54117S ●●	Shiny Black Graphite Pattern
HP54118 ●●	Matte Copper Pattern
HP54119 ●●	Matte Camo Pattern
HP54MIX ●●	HP54116 (3), HP54117 (3), HP54118 (3), and HP54119 (3)
HP54MIXS ●●	HP54116S (3) and HP54117S (3)

4-Point Ratchet Part No.	Color
HP54110 ●●	White
HP54111 ●●	Black
HP54113 ●●	Slate Gray
HP54120 ●●	Red
HP54130 ●●	Yellow
HP54131 ●●	Hi-Vis Lime
HP54135 ●●	Green
HP54141 ●●	Hi-Vis Orange
HP54160 ●●	Blue
HP54170 ●●	Hi-Vis Pink
HPR541	Replacement Suspension
HP6PTSUS	6-Point Suspension Strap



There's more to see at
PYRAMEXSAFETY.COM

(P) 800.736.8673 | (F) 901.861.4967

Ridgeline head protection meets ANSI Z89.1 (●), Type 1, Class E, G, and C. Options also meet Canadian CSA Z94.1-2015 (●) standards. Hi-vis colors have been tested for the "HV" mark.



PYRAMEX
Perform At Your Peak

Ridgeline® Full Brim

Materials

Shell: high impact acrylonitrile-butadiene-styrene (ABS)

Suspension: high density polyethylene (HDPE) & high impact nylon

Sweat band: polyester fabric & polyurethane (PU) foam

General Specifications

Weight: 378 gm

Shell thickness: 1.7 - 4 mm

Dimensions: 31 cm x 27 cm x 15.2 cm

Suspension adjust sizing: 6.5 - 8

Suspensions: 4-point suspension may be converted to 6-point suspension with optional strap

Standards: ANSI/ISEA Z89.1-2014 and Cert. Mod. - CAN/CSA Z94.1-15

Types: Type 1

Classes: Class E, G, and C

Optional features: hi-vis colors (HV), lower temperature (LT), higher temperature (HT)

Markings

Types: Type 1 offers protection to the top of the head

Classes: Class E (electrical) rated for 20,000 volts | Class G (general) rated for 2,200 volts | Class C (conductive) does not offer electrical protection

HV: meets all requirements for high visibility

LT: provides protection at low temperatures -22°F

HT: provides protection at high temperatures 140°F

Date code: indicated month and year when the shell was molded – does not indicate service life



Product Guidelines

Maximum service life of 5 years (shell) & 1 year (suspension) from the time of first use

Never alter or modify the shell or suspension system

Inspect the hard hat each time before use and replace if there is ANY sign of damage

Replace hard hat after it receives a considerable impact

Accessories such as liners have not been tested to the requirement of this standard

Clean only with mild soap and lukewarm water

Store hard hat in a clean, dry place that is out of direct sunlight

Do not use paints, chemicals, adhesives, gasoline or similar substances on the hard hat

Labels are acceptable if they do not affect a hard hat's protective rating or make it difficult to find damage



There's more to see at
PYRAMEXSAFETY.COM

(P) 800.736.8673 | (F) 901.861.4967