

# LEGACY®

ECONOMICAL & FASHIONABLE SPECTACLE

**PART**

SB2310S\*

SB2320S\*

**LENS**
 Clear

 Gray

- Soft PVC nosepiece.
- Adjustable temples with four settings.
- Lenses coated for superior scratch resistance, provides 99.9% protection against harmful UV rays.

**GENERAL SPECIFICATION**

Bridge: 3.0cm

Lens Base: 7 curve

Lens Size Diagonal: 14.5cm

Lens Size Vertical: 5.0cm

Lens Thickness: 2.0mm

Overall Length (Lens-Tip): 10cm - 11.4cm

Overall Width (Hinge-Hinge): 14.6cm

PD: 7.0cm

Weight: 27.2gm

# LEGACY®

ECONOMICAL & FASHIONABLE SPECTACLE



**PACKAGING**

Polybag: 1pc

Inner Box: 12 pcs

Case: 300 pcs

COMPONENT	MATERIAL	FEATURES
Lens	Polycarbonate	6 1/2 base curve, permanently attached to lens
Frame	N/A	N/A
Side Shield	Polycarbonate	Integral to lens
Nose Piece	V bridge -nylon Pad- Polycarbonate Vinyl Chloride	Integral to lens snaps to nose bridge
Sleeve (on temple)	N/A	N/A
Temple	Nylon	Adjustable to 4 lengths positions
Temple tip	Nylon	Adjustable
Hinge	Nylon	3 barrel type, integral to temple
Screw	Stainless steel	Standard hinge screw

PART	LENS	LENS MARKING	FRAME MARKING
SB2310S	 Clear	P Z87 + U6	P Z87 +
SB2320S	 Gray	P Z87 + U6 L3	P Z87 +

**LENS MARKING****Symbols:**

P: Manufacturer's mark

Z87: ANSI standard for Eye and Face protection devices

+: High Impact

H: Small Head Size

S: Special Purpose

**UV Filter Transmittance:**

U2: Max Effective Far UV= .1% / Max Near UV= 3.7%

U2.5: Max Effective Far UV= .1% / Max Near UV= 2.3%

U3: Max Effective Far UV= .07% / Max Near UV= 1.4%

U4: Max Effective Far UV= .04% / Max Near UV= .5%

U5: Max Effective Far UV= .02% / Max Near UV= .2%

U6: Max Effective Far UV= .01% / Max Near UV= .1%

**Visible Light Filters:**

L1.3: 85% Max. Visible Light

L1.7: 55% Max. Visible Light

L2.5: 29% Max. Visible Light

L3: 18% Max. Visible Light

**FRAME MARKING****Symbols:**

P: Manufacturer's mark

Z87: ANSI standard for Eye and Face protection devices

+: High Impact