

AZERA™

SLEEK SLIMLINE PROTECTION



PART

SB4410D*

SB4420D*

SB4430D*

SP4410D*

LENS

Clear

Gray

Amber

Clear

- Sleek slimline protection.
- Lenses filter 99.9% of harmful UV rays.
- Straight back temples provide outstanding fit.
- Built-in rubber flange nose piece provides all day comfort.

GENERAL SPECIFICATION

Bridge: 18.9mm

Closest Point Between Lens: 18.9mm

Closest Point Between Temples: 90mm

Lens Base: 8 curve

Lens Size Diagonal: 53mm

Lens Size Vertical: 34mm

Lens Thickness: 2.2mm

Overall Length (Lens-Tip): 124mm

Overall Width (Hinge - Hinge): 146mm

PD: 75.8mm

Weight: 26g





AZERA™

SLEEK SLIMLINE PROTECTION

PACKAGING

Polybag: 1pc
Inner Box: 12 pcs
Case: 300 pcs

COMPONENT	MATERIAL	FEATURES
Lens	Polycarbonate	8 base curve, cut lens attached to frame
Frame	Polycarbonate	The frame encompasses the whole lens
Temple	Polycarbonate	N/A
Temple Tip	Hard Rubber	N/A
Nose Piece	Rubber	N/A
Screw	Stainless Steel	Standard Hinge Screw

PART	LENS	LENS MARKING	FRAME MARKING
SB4410D	 Clear	P Z87 + U6	P Z87 +
SB4420D	 Gray	P Z87 + U6 L3	P Z87 +
SB4430D	 Amber	P Z87 + U6	P Z87 +
SP4410D	 Clear	P Z87 + U6	P Z87 +

LENS MARKING

Symbols:

P: Manufacturer's mark
 Z87: ANSI standard for Eye and Face protection devices
 +: High Impact
 H: Small Head Size
 S: Special Purpose

UV Filter Transmittance:

U2: Max Effective Far UV= .1% / Max Near UV= 3.7%
 U2.5: Max Effective Far UV= .1% / Max Near UV= 2.3%
 U3: Max Effective Far UV= .07% / Max Near UV= 1.4%
 U4: Max Effective Far UV= .04% / Max Near UV= .5%
 U5: Max Effective Far UV= .02% / Max Near UV= .2%
 U6: Max Effective Far UV= .01% / Max Near UV= .1%

Visible Light Filters:

L1.3: 85% Max. Visible Light
 L1.7: 55% Max. Visible Light
 L2.5: 29% Max. Visible Light
 L3: 18% Max. Visible Light

FRAME MARKING

Symbols:

P: Manufacturer's mark
 Z87: ANSI standard for Eye and Face protection devices
 +: High Impact