

PMXTREME® READERS

OPTIMAL STYLE IN SAFETY EYEWEAR



PART	LENS
SB6310SPR15*	<input type="checkbox"/> Clear +1.5
SB6310SPR20*	<input type="checkbox"/> Clear +2.0
SB6310SPR25*	<input type="checkbox"/> Clear +2.5

- Built-in rubber nose piece provides all day comfort.
- Includes black lanyard cord for extra security while wearing.
- Rubber temple tips keep eyewear secure for the active worker.
- Extreme style in safety eyewear, with clean lines and sports appeal.
- Ventilated, straight-back flexible temples provide cool, pressure-free fit.
- Scratch resistant polycarbonate lenses provide maximum vision protection, filter out 99% of harmful UV rays.

GENERAL SPECIFICATION

Bridge: 14mm

Lens Base: 9 Curve

Lens Size Diagonal: 78mm

Lens Size Vertical: 46mm

Lens Thickness: 2.2mm

Overall Length [Lens-Tip]: 103mm

Overall Width [Hinge-Hinge]: 140mm

PD: 72mm

Weight: 27gm

PMXTREME® READERS

OPTIMAL STYLE IN SAFETY EYEWEAR




PACKAGING

Polybag: 1pc

Inner Box: 6 pcs

Case: 150 pcs

COMPONENT	MATERIAL	FEATURES
Lens	Polycarbonate	9 base curve, molded lens attached to the frame
Frame	Nylon	Half Frame
Nose Piece	Rubber	N/A
Sleeve (on temples)	Hard Rubber	N/A
Temple	Nylon	N/A
Hinge Screw	Nickel Silver	Standard hinge screw

PART	LENS	LENS MARKING	FRAME MARKING
SB6310SPR15	 Clear +1.5	P + U6	P Z87 + 2
SB6310SPR20	 Clear +2.0	P + U6	P Z87 + 2
SB6310SPR25	 Clear +2.5	P + U6	P Z87 + 2

LENS MARKING

Symbols:

P: Manufacturer's mark

Z87: ANSI standard for Eye and Face protection devices

+: High Impact

H: Small Head Size

S: Special Purpose

UV Filter Transmittance:

U2: Max Effective Far UV= .1% / Max Near UV= 3.7%

U2.5: Max Effective Far UV= .1% / Max Near UV= 2.3%

U3: Max Effective Far UV= .07% / Max Near UV= 1.4%

U4: Max Effective Far UV= .04% / Max Near UV= .5%

U5: Max Effective Far UV= .02% / Max Near UV= .2%

U6: Max Effective Far UV= .01% / Max Near UV= .1%

Visible Light Filters:

L1.3: 85% Max. Visible Light

L1.7: 55% Max. Visible Light

L2.5: 29% Max. Visible Light

L3: 18% Max. Visible Light

FRAME MARKING

Symbols:

P: Manufacturer's mark

Z87: ANSI standard for Eye and Face protection devices

+: High Impact