

PMXTREME® Rx

Optimal Style In Safety Eyewear



Black Frame with Black Cord

Part	Lens
SB6310STRX•	Clear Anti-Fog
SB6320STRX•	Gray Anti-Fog

- Built-in rubber nose piece.
- Includes black lanyard cord.
- Rx insert attached inside the frame.
- Ventilated, straight-back flexible temples.
- Rubber temple tips keep eyewear secure for the active worker.
- Includes RX insert which, accommodates -3.0 to +3.0 prescription lenses.
- Scratch resistant polycarbonate lens provides 99% UVA/B/C protection.

GENERAL SPECIFICATION



Bridge: 14mm
Lens Base: 9 Curve
Lens Size Diagonal: 78mm
Lens Size Vertical: 46mm
Lens Thickness: 2.2mm
Overall Length (Lens-Tip): 103mm
Overall Width (Hinge-Hinge): 146mm
PD: 72mm
Weight: 29gm

PACKAGING

Polybag: 1pc
Inner Box: 6 pcs
Case: 150 pcs

PMXTREME[®] Rx

COMPONENT	MATERIAL	FEATURES
Lens	Polycarbonate	9 curve lens wide angle
Frame	Nylon	Half Frame
Nose Piece	Rubber	N/A
Rx Insert	TR90	N/A
Temple	Nylon	N/A
Temple Tip	Hard Rubber	N/A
Screw	Stainless Steel	Standard hinge screw

PART	LENS	LENS MARKING	FRAME MARKING
SB6310STRX	 Clear Anti-Fog	P + U6	P Z87 +
SB6320STRX	 Gray Anti-Fog	P + U6 L3	P Z87 +

LENS MARKING

Symbols:

P: Manufacturer's mark
 Z87: ANSI standard for Eye and Face protection devices
 +: High Impact
 H: Small Head Size
 S: Special Purpose

UV Filter Transmittance:

U2: Max Effective Far UV= .1% / Max Near UV= 3.7%
 U2.5: Max Effective Far UV= .1% / Max Near UV= 2.3%
 U3: Max Effective Far UV= .07% / Max Near UV= 1.4%
 U4: Max Effective Far UV= .04% / Max Near UV= .5%
 U5: Max Effective Far UV= .02% / Max Near UV= .2%
 U6: Max Effective Far UV= .01% / Max Near UV= .1%

Visible Light Filters:

L1.3: 85% Max. Visible Light
 L1.7: 55% Max. Visible Light
 L2.5: 29% Max. Visible Light
 L3: 18% Max. Visible Light

FRAME MARKING

Symbols:

P: Manufacturer's mark
 Z87: ANSI standard for Eye and Face protection devices
 +: High Impact