

THE ZONE®

Striking Good Looks



Black Frame

Part

SB910E•

SB920E•

Lens

Clear

Gray

- Lightweight nylon frame combined with striking design.
- Lenses coated for superior scratch resistance, provides 99.9% protection against harmful UV rays.

GENERAL SPECIFICATION

Bridge: 10.8mm

Lens Base: 8.25 Curve

Lens Size Diagonal: 66mm

Lens Size Vertical: 44mm

Lens Thickness: 2.2mm

Overall Length (Lens-Tip): 152mm

Overall Width (Hinge-Hinge): 130mm

PD: 68mm

Weight: 29gm



PACKAGING

Polybag: 1pc

Inner Box: 12 pcs

Case: 300 pcs

COMPONENT	MATERIAL	FEATURES
Lens	Polycarbonate	Full eye protection 8 curve lens
Frame	Nylon 6.6	Dual lens, matte finish
Nose Piece	Nylon 6.6	Integral to frame
Temple	Nylon 6.6	Spatula, fixed length
Hinge	Nylon 6.6	3 barrel type, integral to frame
Screw	Stainless Steel	Standard hinge screw

PART	LENS	LENS MARKING	FRAME MARKING
SB910E	 Clear	P Z87 + H U6	P Z87 +
SB920E	 Gray	P Z87 + H U6 L2.5	P Z87 +

LENS MARKING**Symbols:**

P: Manufacturer's mark

Z87: ANSI standard for Eye and Face protection devices

+: High Impact

H: Small Head Size

S: Special Purpose

W: Welding Filter

UV Filter Transmittance:

U2: Max Effective Far UV= .1% / Max Near UV= 3.7%

U2.5: Max Effective Far UV= .1% / Max Near UV= 2.3%

U3: Max Effective Far UV= .07% / Max Near UV= 1.4%

U4: Max Effective Far UV= .04% / Max Near UV= .5%

U5: Max Effective Far UV= .02% / Max Near UV= .2%

U6: Max Effective Far UV= .01% / Max Near UV= .1%

Visible Light Filters:

L1.3: 85% Max. Visible Light

L1.7: 55% Max. Visible Light

L2.5: 29% Max. Visible Light

L3: 18% Max. Visible Light

FRAME MARKING**Symbols:**

P: Manufacturer's mark

Z87: ANSI standard for Eye and Face protection devices

+: High Impact