



**PYRAMEX**  
Perform At Your Peak™

**Endeavor® Plus** **ANSI** **CSA**



RUBBER  
NOSEPIECE



DIELECTRIC



CO-INJECTED  
TEMPLES



ADJUSTABLE  
NOSEPIECE



Lightweight and durable protective eyewear

Built-in brow guard

Special dielectric hinge design

Curved, co-injected temples

One-piece wraparound lens

Soft and adjustable nosepiece

Part No.	Black and Green Temples
SBGR9610S ●●	Clear
SBGR9620S ●●	Gray
SBGR9680S ●●	I/O Mirror



Part No.	Black and Gray Temples
SBG9610S ●●	Clear
SBG9610ST ●●	AF Clear <b>H2X</b>
SBG9620S ●●	Gray
SBG9620ST ●●	AF Gray <b>H2X</b>
SBG9630S ●●	Amber
SBG9680S ●●	I/O Mirror



Part No.	Black and Pink Temples
SBP9610S ●●	Clear

There's more to see at  
**PYRAMEXSAFETY.COM**

(P) 800.736.8673 | (F) 901.861.4967

All safety eyewear meets ANSI Z87.1+ standards (●) and provide 99% protection from harmful UV rays. All lenses are hard coated polycarbonate scratch-resistant unless otherwise noted. Some options meet Canadian (CSA Z94.3) (●) standards.



**PYRAMEX**  
Perform At Your Peak™

## Endeavor® Plus

### General Specifications

Weight: 23.5 gm  
 Bridge: 13.6 mm  
 Lens base: 9.5 curve  
 Lens size diagonal: 74 mm  
 Lens size vertical: 44.2 mm  
 Lens thickness: 1.8 mm  
 Overall length (lens - tip): 155 mm  
 Overall width (hinge - hinge): 124.7 mm  
 Closest point between temple tips: 75 mm

### Materials

Lens: polycarbonate  
 Temples: polycarbonate & thermoplastic elastomers (TPE)  
 Hinge: polycarbonate  
 Side shields: polycarbonate  
 Nosepiece: thermoplastic rubbers (TPR)

Part No.	Lens Marking	Temple Marking
SBG9610S	P Z87 + U6	P Z87 + / P c SEI CAN/CSA Z94.3-15
SBG9610ST	P Z87 + U6	P Z87 + / P c SEI CAN/CSA Z94.3-15
SBG9620S	P Z87 + U6 L2.5	P Z87 + / P c SEI CAN/CSA Z94.3-15
SBG9620ST	P Z87 + U6 L2.5	P Z87 + / P c SEI CAN/CSA Z94.3-15
SBG9630S	P Z87 + U6	P Z87 + / P c SEI CAN/CSA Z94.3-15
SBG9680S	P Z87 + U6 L1.7	P Z87 + / P c SEI CAN/CSA Z94.3-15
SBP9610S	P Z87 + U6	P Z87 + / P c SEI CAN/CSA Z94.3-15
SBGR9610S	P Z87 + U6	P Z87 + / P c SEI CAN/CSA Z94.3-15
SBGR9620S	P Z87 + U6 L2.5	P Z87 + / P c SEI CAN/CSA Z94.3-15
SBGR9680S	P Z87 + U6 L1.7	P Z87 + / P c SEI CAN/CSA Z94.3-15

### Lens Marking Symbols

P: Manufacturer's mark  
 Z87: ANSI standard for eye and face protection devices

#### UV Filter Transmittance

U6: .01% max effective far UV • .1% max near UV

#### Visible Light Filters

L1.7: 55% max visible light  
 L2.5: 29% max visible light

### Temple Marking Symbols

P: Manufacturer's mark  
 Z87: ANSI standard for eye and face protection devices

+ : High impact

c SEI CAN/CSA Z94.3-15: CAN/CSA standard for eye and face protection devices



There's more to see at  
**PYRAMEXSAFETY.COM**

(P) 800.736.8673 | (F) 901.861.4967