







Black Frame

- | Part | Lens | |
|-------------|---|-----------------|
| VGSB1126DB• |  | Forest Gray |
| VGSB1165DB• |  | Ice Blue Mirror |
| VGSB1170DB• |  | Silver Mirror |

Brown Frame






- | Part | Lens | |
|--------------|---|--------------------|
| VGSBR1118DB• |  | Bronze |
| VGSBR1156DB• |  | Multi-Color Mirror |

- Flexible rubber nosepiece.
- Dual-injected straight-back temples.
- Scratch resistant polycarbonate lens provides 99% UVA/B/C protection.
- Packaged in a Venture Gear branded polybag with retail tag.

GENERAL SPECIFICATION
Bridge: 17mm
Lens Base: 8 Curve
Lens Size Diagonal: 72mm
Lens Size Vertical: 41mm
Lens Thickness: 2mm
Overall Length (Lens-Tip): 131mm
Overall Width (Hinge-Hinge): 129+/-1mm
Weight: 24.4gm
Closest point between lenses: 11mm
Closest point between temple tips: 95mm+/-5mm

PACKAGING
Static sticker on bottom left lens
Temple tag with UPC code label
Sold individually in Venture Gear branded polybag
Box: 12 pcs
Case: 300 pcs

COMPONENT	MATERIAL	FEATURES
Lens	Polycarbonate	8 base dual lens
Frame	PC	Lightweight
Screw	Stainless steel	Standard hinge screw

PART	LENS	LENS MARKING	FRAME MARKING
VGSB1126DB	 Forest Gray	P + S	P Z87 +
VGSB1165DB	 Ice Blue Mirror	P + S	P Z87 +
VGSB1170DB	 Silver Mirror	P + S	P Z87 +
VGSBR1118DB	 Bronze	P + S	P Z87 +
VGSBR1156DB	 Multi-Color Mirror	P + S	P Z87 +

LENS MARKING

Symbols:
 P: Manufacturer's mark
 Z87: ANSI standard for Eye and Face protection devices
 +: High Impact
 H: Small Head Size
 S: Special Purpose

UV Filter Transmittance:

U2: Max Effective Far UV= .1% / Max Near UV= 3.7%
 U2.5: Max Effective Far UV= .1% / Max Near UV= 2.3%
 U3: Max Effective Far UV= .07% / Max Near UV= 1.4%
 U4: Max Effective Far UV= .04% / Max Near UV= .5%
 U5: Max Effective Far UV= .02% / Max Near UV= .2%
 U6: Max Effective Far UV= .01% / Max Near UV= .1%

Visible Light Filters:

L1.3: 85% Max. Visible Light
 L1.7: 55% Max. Visible Light
 L2.5: 29% Max. Visible Light
 L3: 18% Max. Visible Light

FRAME MARKING

Symbols:
 P: Manufacturer's mark
 Z87: ANSI standard for Eye and Face protection devices
 +: High Impact
 P c SEI CAN/CSA Z94.3-07: CAN/CSA for protection devices