

Drone®

Stylish Half-Frame Design



Black Frame

Part	Lens
VGSB8310ST ●●●	Clear Anti-Fog
VGSB8320ST ●●●	Gray Anti-Fog
VGSB8370S ●●●	Silver Mirror

- Half-frame design.
- Stylish, dual injected temples.
- Adjustable rubber nosepiece.
- Anti-fog, scratch resistant polycarbonate lens provides 99% UVA/B/C protection.
- Passes MIL-PRF 32432 High Velocity Impact Standards.
- Packaged in a Venture Gear Tactical branded box with temple tag for counter top or pegboard display.




GENERAL SPECIFICATION
Bridge: 18mm
Closest Point Between Lens: 20mm
Closest Point Between Temple Tips: 80 + 5mm
Lens Base: 8 Curve
Lens Size Diagonal: 78mm
Lens Size Vertical: 45mm
Lens Thickness: 2.0mm
Overall Length (Lens-Tip): 130mm
Overall Width (Hinge-Hinge): 130 + 1mm
Weight: 24.6gm

PACKAGING

Sold individually in a Venture Gear Tactical branded box

Case: 60 pcs

COMPONENT	MATERIAL	FEATURES
Frame	PC	Ventilation allows air to circulate and prevent fogging
Temple	PC	n/a
Temple tip	TPR	Rubber tips provides comfort fit
Nose Piece	TPR + wire	Adjustable provides fits for a broad range of bridge size
Screw	Stainless Steel	Standard Hinge Screw

PART	LENS	LENS MARKING	FRAME MARKING
VGSB8310ST	 Clear Anti-Fog	P + S	P Z87 + / P c SEI CAN/CSA Z94.3-07
VGSB8320ST	 Gray Anti-Fog	P + S	P Z87 + / P c SEI CAN/CSA Z94.3-07
VGSB8370S	 Silver Mirror	P + S	P Z87 + / P c SEI CAN/CSA Z94.3-07

LENS MARKING**Symbols:**

P: Manufacturer's mark

Z87: ANSI standard for Eye and Face protection devices

+: High Impact

H: Small Head Size

S: Special Purpose

UV Filter Transmittance:

U2: Max Effective Far UV= .1% / Max Near UV= 3.7%

U2.5: Max Effective Far UV= .1% / Max Near UV= 2.3%

U3: Max Effective Far UV= .07% / Max Near UV= 1.4%

U4: Max Effective Far UV= .04% / Max Near UV= .5%

U5: Max Effective Far UV= .02% / Max Near UV= .2%

U6: Max Effective Far UV= .01% / Max Near UV= .1%

Visible Light Filters:

L1.3: 85% Max. Visible Light

L1.7: 55% Max. Visible Light

L2.5: 29% Max. Visible Light

L3: 18% Max. Visible Light

FRAME MARKING**Symbols:**

P: Manufacturer's mark

Z87: ANSI standard for Eye and Face protection devices

+: High Impact

P c SEI CAN/CSA Z94.3-07: CAN/CSA for protection devices