

CH Series Portable Quartz Infrared Heater



Chain mounted
CH 2212-1C



MODEL CH 2212-1C has two 1000 Watt elements that can be switched on / off by toggle switches to produce 1000 Watts or 2000 Watts of heat. - 15' cord and NEMA 5-20 molded plug.

MODEL CH 6424-1C has two sets of 1425 Watt elements that can be switched on / off by toggle switches to produce 2850 Watts or 5700 Watts of heat. - 15' cord and NEMA L6-30 twist lock plug.

- 60° symmetrical heat pattern.
- Interior or protected outdoor use only.
- Made in U.S.A.

- Quartz tubes and built in wire guards included.
- GOLD anodized Aluminum reflector and end caps.



Portable Cart Unit
CH 6424-1C
with FHK-1 Cart

| MFG CATALOG NUMBER | MFG MODEL NUMBER | KW | BTUs | VOLTS | PHASE | AMPS | WT. (LBS) | LIST | |
|--------------------|------------------|---------------|--------------|-------|-------|-------------|-----------|-------------|------------|
| 08840910 | CH-2212-1C | 2.0 / 1.0 | 6826 / 3413 | 120 | 1 | 16.7 / 8.35 | 16 | 646 | |
| 08841010 | CH-6424-1C | 5.7 / 2.85 | 19454 / 9727 | 240 | 1 | 23.8 / 11.9 | 31 | 1065 | |
| 08524002 | FHK-1 | OPTIONAL CART | | | | | | 20 | 157 |

WARNING: This product can expose you to chemicals including nickel which is known to the State of California to cause cancer, and chromium, which is known to the State of California to cause birth defects and/or reproductive harm. For more information go to www.P65Warnings.ca.gov.



Note: CH-2212-1C operates with a 20- Amp molded plug.




Note: CH-6424-1C operates with a 30- Amp twist lock plug.

Listed for overhead operation

PCH Series Portable Quartz Infrared Spot Heater

Portable Infrared Instant On-Off Heat Gun



Width: 53"
Height: 2-6"
Depth: 28"



Features

- Suitable for portable spot heat or for curing clear coat paint
- Height adjustable from 2' to 4'
- On-Off rocker switch standard
- 4 casters included; Tip-Over power cutoff safety switch
- 60° symmetrical heat pattern
- 5/8" diameter quartz tube included
- Average element life is 5000 hours
- Bright Aluminum reflector and end caps
- 20 gauge powder coated Steel housing
- 15' long, 3 wire (14/3) cordset with standard 3 pring NEMA 5-20P
- Made in U.S.A.

WARNING: This product can expose you to chemicals including nickel which is known to the State of California to cause cancer, and chromium, which is known to the State of California to cause birth defects and/or reproductive harm. For more information go to www.P65Warnings.ca.gov.

| MFG CATALOG NUMBER | MFG MODEL NUMBER | WATTS | BTUs | VOLTS | PHASE | WT. (LBS) | LIST |
|--------------------|------------------------------|-------|------|-------|-------|-----------|------------|
| 08841110 | PCH-48C | 1500 | 5120 | 120 | 1 | 30 | 608 |
| 58763001 | REPLACEMENT ELEMENT ASSEMBLY | | | | | | 100 |



Features

- Provides instant spot heat in a controlled pattern
- Spot cure retouched paint and other finishes
- De-wrinkle or relax materials such as cloth-vinyl-leather
- T-3 Tungsten IR lamp
- Ergonomically friendly, easy-grip handle
- 20' long, 18/3 grd. cordset with GFCI plug
- Made in U.S.A.

WARNING: This product can expose you to chemicals including nickel which is known to the State of California to cause cancer, and chromium, which is known to the State of California to cause birth defects and/or reproductive harm. For more information go to www.P65Warnings.ca.gov.

| MFG CATALOG NUMBER | MFG MODEL NUMBER | WATTS | VOLTS | AMPS | WT. (LBS) | LIST |
|--------------------|------------------|-------|-------|------|-----------|-------------|
| 05922802 | RHG-1012A | 1000 | 120 | 8.4 | 3 | 2295 |

Portable Electric Infrared Heat Panels

Features

- Portable panels are built to withstand rigors of industrial and heavy-commercial applications, such as auto collision repair shops.
- 20 gauge steel frame, base, and housing construction.
- 3" steel casters for high stability and ease of mobility
- Gold anodized Aluminum reflectors and end caps allow 10% faster cure time than polished Aluminum reflectors, especially in paint and dust-laden atmospheres.
- Elements achieve full temperature in less than 2 minutes
- Fused disconnect switches are installed on the back of each unit.
- Units are positioned with adjustable hinges allowing the user to use direct heat more precisely to the target area.
- Gentle but effective medium-wave radiant heat can quickly boost, flash-off, or cure a variety of finishes, and lessens the chance of blistering and/or overheating the coating.
- Medium-wave infrared heating elements are also effective for flash-off of water-based clear coatings being mandated by environmental agencies in many states.
- Made in U.S.A.



WARNING: This product can expose you to chemicals including nickel which is known to the State of California to cause cancer, and chromium, which is known to the State of California to cause birth defects and/or reproductive harm. For more information go to www.P65Warnings.ca.gov.

General Curing Guidelines

| Material Type | Solvent Based Primer | Water Based Primer | Two Component Primer | Water Based Clear Coat | Acrylic enamel & Polyurethane Clear Coat | Urethane Clear Coat & High Solids Top Coat |
|---------------|----------------------|--------------------|----------------------|------------------------|--|--|
| Curing Time | 3-5 mins | 3-6 mins | 8-20 mins | 3-10 mins | 12-30 mins | 10-30 mins |

Note: Curing times will vary depending on material and shop conditions. This chart is based on distances of 18-24" away from the target area.

Standard Models

| MFG CATALOG NUMBER | MFG MODEL NUMBER | WATTS | VOLTS | AMPS | HEAT SOURCES | CABLE TYPE (20') | DIMENSION (IN.) | | HEATED AREA (IN.) | | WT. (LBS) | LIST |
|--------------------|------------------|--------|-------|------|--------------|------------------|-----------------|--------|-------------------|--------|-----------|-------------|
| | | | | | | | Width | Height | Width | Height | | |
| 08841202 | HP-5-QT | 4,800 | 240 | 20 | 4 | 12-3 SO | 44 3/8 | 56 1/2 | 40 | 44 | 116 | 3123 |
| 08841302 | HP-6-QT | 6,400 | | 26.7 | 4 | | 66 3/8 | 89 1/2 | 61 | 77 | 141 | 3610 |
| 08841402 | HP-11-QT | 11,200 | | 46.7 | 7 | | 6-3 SO | | | | 225 | 6646 |