



UT Series - Low Voltage



Features


- Vertical or horizontal mounting
- Long life sealed contacts
- Does not contain Mercury
- Leveling not required
- Fahrenheit and Celsius temperature scales
- 2-3°F rated differential
- Anticipator (except UT9001)

Standard Models

UPC# 686334	MODEL	DESCRIPTION	VOLTAGE	TERMINALS	SWITCHES	LIST
523059	UT1001	Heat Only	24VAC or MV	R & W	None	17.60
523066	UT3001	Cool Only	24 VAC	R, Y & G	Cool/Off Fan/Auto	18.15
523134	UT6001	Deadband	24 VAC	R, W & Y	None	19.25
523073	UT8001	Heat/Cool	24 VAC	RC, RH, W, Y, & G	Heat/Off/Cool Fan/Auto	19.25
523110	UT9001	Heat Only	Millivolt	R & W	None	17.60

Master Carton: 50 pcs, 17 lbs, 19" x 11.5" x 9"

RK Series - Low Voltage



Features

- Heat only models
- Positive off
- Does not contain Mercury
- Leveling not required
- Long life sealed contacts
- Fahrenheit and Celsius temperature scales
- 2-3°F rated differential

Standard Models

UPC # 686334	MODEL	DESCRIPTION	VOLTAGE	RANGE	ANTICIPATOR	LIST
526012	RK120EAA	Heat Only	24VAC or MV	50°-90°F	Yes	17.60
526203	RK124EAA	Heat Only	24VAC or MV	35°-75°F	Yes	17.60
526050	RK130EAA	Heat Only	Millivolt	50°-90°F	No	14.85
526326	RK134EAA	Heat Only	Millivolt	35°-75°F	No	14.85
526142	RKWP1AA	Wall Plate	NA	NA	NA	3.85

Master Carton: 100 Pcs, 24 lbs, 16.5" x 15" x 8"

Low Voltage Relays



Two switch unit shown.

Features

- Snap action switch
- 1/2" male conduit spud
- 45 second average time delay
- Temperature range - 50° - 90°F
- Built-In transformer

Standard Models

UPC# 686334	MODEL	PRIMARY VOLTAGE	DESCRIPTION	LIST
260039	24A05A-1	120 Volts	Single Switch, single throw with In-Built Transformer for remote mounting or in a factory provided optional enclosure	179
260046	24A05E-1	208 Volts		
260053	24A01G-3	240 Volts		
260107	24A06G-1	240 Volts	Two switch, single throw with In-Built Transformer, 25 Amps per switch	264

TG Series Thermostat Guards



Features

- 8 tumbler locks

Standard Models

UPC# 686334	MODEL	DESCRIPTION	LIST
589123	TG1	Plastic Stat Guard/ 6.25" x 3.625" x 3.25" Opening	32
589109	TG1B	Metal Stat Guard/ 5.25" x 4.625" x 3" Opening	57
589130	TG2	Plastic Stat Guard/ 5.25" x 4.625" x 3.25" Opening	37
589161	TG2B	Metal Stat Guard/ 6.25" x 3.625" x 3.25" Opening	57
589116	TG3	Plastic Stat Guard/ 8.125" x 4.625" x 3.625" Opening	37
589178	TG3B	Metal Stat Guard/ 6.75" x 4.50" x 3.50" Opening	70
523615	TG4	Plastic Stat Guard / 3.50" x 3.937" x 1.75" Opening	37
523622	TG5	Plastic Stat Guard / 5" x 3.31" x 1.75" Opening	37
523639	TG6	Plastic Stat Guard / 5.75" x 4.625" x 1.75" Opening	37