

Product Data Sheet

No. **27043** - 06/13

WIRE ROPE, CHAIN & CABLE LUBE

PRODUCT NUMBERS: 7043 - 12 OZ NET WT. AEROSOL

I. GENERAL DESCRIPTION

Description: This high grade lubricating oil is fortified with molybdenum disulfide. Penetrates inaccessible areas and provides superior lubrication where temperature and pressure will break down ordinary lubricants.

Benefits: Penetrates deep between roller-chain drive bushings. Reduces the stress of start-ups and high temperature breakdowns. Travels deep into wire ropes, exposed gear boxes and along cabling. Reduces wear and increases chain life. Excellent water displacing characteristics provide corrosion protection.

Application: For lubrication of hoists and hoist chains, saws, conveyors, link and roller assemblies, chain drives and pins, bushings, clippers, cables, gear boxes, and any other application where high grade light oil is necessary.

Directions: Align spray head with black mark on valve rim to ensure complete evacuation. Shake can vigorously for 30 seconds before use and intermittently thereafter. Hold can 8 to 10 inches from surface and spray area thoroughly. Use at room temperature (70° F / 21° C) for best results. For use in the manufacturing process only. Do not use on electrical equipment or machinery while in operation.

Limitations: Please refer to the Safety Data Sheet for specific information on material hazards, etc.

Packaging:

Aerosol:

Cans (211x604)
12 cans/case

12 oz. net wt. (340 grams)
14 lbs. (6.4 kg)

15.0 fl. oz. (444 ml)
0.47 CF (0.013 CM)

II. CHARACTERISTICS & PROPERTIES

Specifications:

None

Appearance:

Non-foaming thick liquid / grease

Color:

Black

Odor:

Mild hydrocarbon.....

Performance and Chemical Properties:**Aerosol**

Weight per gallon	6.4 lbs.
Specific gravity	0.8
Flammability: Label marking	Extremely Flammable
Flash point.....	< 0° F (-18° C)
Operating temperature range.....	40° to 110° F (5° to 43° C)
Performing temperature range.....	-20° to 300° F (-29° to 149° C)
Active ingredients by weight.....	29%
Volatile Organic Compound level.....	71%
EPA VOC% Limit.....	Not Regulated
CARB VOC% Limit.....	I&I Exempt
FALEX EP Test (Fallen Load)	4500 lbs
FALEX FLC Test (Lubricity).....	> 200 lbs.
Penetrating ability.....	Good
Corrosion protection.....	Good

Base Materials:

Lubricating system	Moly Grease
Solvents (top two)	Petroleum Distillates, Petroleum Naptha
Propellant.....	Hydrocarbon

III. SHIPPING, STORAGE AND HEALTH

UN number.....	UN1950
Proper Shipping Description	Aerosols
Hazard Class.....	2.1
Packing Group	N/A
Limited Quantity	Yes
Warehouse storage level number	NFPA 30B Level 2
Storage temperature	32° to 120°F (0° to 49°C)
Shelf life	1 to 5 years

HMIS ratings

Health.....	1
Fire	4
Reactivity.....	1

IV. MISCELLANEOUS

Contains no Ozone Depleting Substances (O.D.S.)

V. WARRANTY

1-year performance warranty on all products from date of purchase. Report to home office or local Aervoe representative for examination. Because Seller cannot control Buyer's handling or use of product, Seller makes no warranty expressed or implied when not used or stored in accordance with directions. Seller shall not be liable for cost of labor, incidental or consequential damages, and this warranty is limited to replacement of product or credit of purchase.

NO. 27043 - 06/13